

TEST REPORT

CLIENT Egetaepper a/s

TEST METHOD CONDUCTED

ASTM D5252 (Heavy Ball) Standard Practice for the Operation of the Hexapod Tumble Drum Tester



DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	Epoca Silky wt			
CONSTRUCTION	Cut Pile			
BACKING	Woven Synthetic			

GENERAL PRINCIPLE

The test specimen is subjected to "Hexapod" tumbling in 2,000 cycle increments. A CRI/SOA upright vacuum was used to make four forward and backward passes along the length of the specimen after each 2,000 cycles.

After the specified total number of cycles is completed, the test specimen is visually assessed by three technicians for appearance change in accordance with the ASTM D7330 "Test Method for Assessment of Surface Appearance Change in Pile Floor Coverings Using Standard Reference Scales".

TEST RESULTS

HEAVY BALL

NUMBER OF CYCLES	APPEARANCE RATING	COLOR CHANGE RATING*	
12,000	4.5	3.5	

*NOTE: At the client's request, an additional rating was reported which assessed perceived color change in the test specimen resulting from pile distortion. The color change rating was done in accordance with AATCC Evaluation Procedure 1, using the Gray Scale for Color Change.

	accordance with AATCC Evaluation Procedure 1, using the Gray scale for Color Change.					
APPEARANCE RATING KEY			COLOR CHANGE RATING KEY			
5	Excellent: No visual change noticeable		5	Negligible or no change		
	Good: Slight change due to disturbance of pile		4	Slight change		
3	Fair: Noticeable change due to pile disturbance or matting		3	Moderate change		
2	Poor: Loss of texture due to pile disturbance and/or matting		2	Considerable change		
1	Very Poor: Severe pile disturbance and/or matting		1	Severe change		

APPROVED BY:





This facility is accredited by the National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code 1923/1. This accreditation does not constitute an enconsement, certification, or approval by NGT or any agency of the United States Government for the productionated. This report is provided for the exclusive use of the port to whom it is additionable it may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing

